

EUROPEAN PATENT OFFICE

Patent Abstracts of Japan

PH	NL	MAI.
030756		DOSSIER

PUBLICATION NUMBER : 2001057028
PUBLICATION DATE : 27-02-01

APPLICATION DATE : 11-08-99
APPLICATION NUMBER : 11227971

APPLICANT : NEC CORP;

INVENTOR : AKIYAMA MINORU;


INT.CL. : G11B 20/12 G11B 20/10

TITLE : DEFECT REPLACING PROCESSING
METHOD AND INFORMATION
RECORDING AND REPRODUCING
DEVICE AND RECORDING MEDIUM

ユーザ領域
(記録再生単位NU個)

ユーザ領域
(記録再生単位NUT-NU個)

ユーザ領域
(記録再生単位NUT個)



ABSTRACT : PROBLEM TO BE SOLVED: To reduce the amount of overhead associated with the internal positioning process of a writing/reading head by providing a spare region corresponding to a continuous region, which is made up with a recorded region and a continuous un-used user region located in front of the recorded region, immediately after the recorded region every time a continuous recording is completed.

SOLUTION: Information to be recorded in recording and reproducing units of physical addresses (NU-1) and NU is recorded in recording and reproducing units of physical addresses (NUT+1) and (NUT+2) and a jump to a spare region, that is continuously secured from the back tip of an original recording region, is combined. Thus, no effect is resulted to the logical addresses of recording and reproducing units after the address (NU+1). In other words, even though effective information exists in a user region after the physical address (NU+1), the defect recording and reproducing units generated later are replaced. Moreover, even though plural defect recording and reproducing units exist in a continuous recording region, only single spare region access is required.

COPYRIGHT: (C)2001,JPO